

TallyGenicom 6600 Series of Line Matrix Printers

the Power
of



Technical Specifications

Printer Features	Open Pedestal 6605 6610 6615	Quiet Pedestal 6605 6610 6615	Zero Tear 6605Z 6610Z 6615Z	Cabinet 6605Q 6610Q 6615Q	6620Q	
Standard						
Integrated Print Management	•	•	•	•	•	
Ribbon Life Monitor	•	•	•	•	•	
Options						
SureStak® Power Stacker					•	
Black back forms paper out sensor	•	•	•	•	•	
Rear Slide Out Paper Drawer					•	
Cabinet Front Access					•	
Pedestal Front Paper Tray	•		•			
Pedestal High Rear Paper Tray	•	•	•			
Pedestal Acoustic Shroud	•	Standard				
Physical Size	Height	36" (914.4mm)	36" (914.4mm)	42" (1066.8mm)	40.5" (1028.7mm)	40.5" (1028.7mm)
	Width	26" (660.4mm)	26" (660.4mm)	26" (660.4mm)	27" (685.8mm)	27" (685.8mm)
	Depth	21.5" (546.1mm)	25" (635mm)	21.5" (546.1mm)	29" (736.6mm)	33" (838mm)
	Shipping Weight	165 lbs (74.842kg) <i>Not including Rear Tray</i>	190 lbs (86.182kg) <i>With Acoustic Shroud</i>	180 lbs (81.646kg)	265 lbs (120.201kg)	300 lbs (136kg) <i>With SureStak Power Stacker</i>
Acoustic (dBA) (per ISO 7779)	6605 - 62	6605 - 58	6605Z - 66	6605Q - 50		
	6610 - 65	6610 - 60	6610Z - 70	6610Q - 50		
	6615 - 68	6615 - 63	6615Z - 70	6615Q - 52	6620Q - 55	
shown by Printer models						
Print Speed (LPM, upper case characters, lower case characters)	6605	6610	6615	6620Q		
	6605Q	6610Q	6615Q			
	6605Z	6610Z	6615Z			
High Speed (draft)	500/428	1000/856	1500/1289	2000/1700		
Data Processing	375/300	750/600	1125/900	1500/1200		
Near Letter Quality	200/154	400/306	600/459	800/615		
Graphics Speed (Inches Per Minute)	60 x 48 dpi	63	125	187	250	
	60 x 72 dpi	42	83	127	167	
	90 x 96 dpi	21	42	61	83	
Paper Feed Speed (Inches Per Second)	12	20	25	38.5		



6600 Open Pedestal

6600Q Cabinet

6600Z Zero Tear

6600 Quiet Pedestal

TallyGenicom 6600 Family of Line Matrix Printers

Character Pitch	5, 6, 6.7, 7.5, 8.3, 8.6, 10, 12, 13.3, 15, 16.7, 17.1, 20 (characters per inch)			
Line Spacing	1.5, 2, 3, 4, 5, 6, 8, 9, 10, 12 (lines per inch – plus variable line spacing)			
Graphics Resolution	180 dpi Horizontal, 144 dpi Vertical (max)			
Dot Size	16.7 mil (.42mm)			
Emulations Standard	Tally ANSI, Genicom ANSI, P5000/P600/P6000, Epson FX-1180, IBM Proprinter, MTPL (Tally Dot Matrix), PGL (TG Version), QMS Code V, Tally Industrial Graphics, PCL-3: HP-2564C, DEC LG01			
Character Sets	47 languages and 43 character sets			
Character Styles	Bold, italic, superscript, subscript, underline, overline, strike-through			
Fonts	Draft, Data Processing, Courier, Gothic, OCR A and B			
Barcodes	Code 39, Code 128, Interleaved 2 of 5, UPC-A, UPC-E, EAN 8, EAN 13, EAN 128, Codabar, MSI, PDF-417, Postnet, Intelligent Mail Barcode (IMB)			
Printer Software	TallyGenicom PrintNet Suite of Tools - remote management software suite - included with the Ethernet option			
Printer Drivers	Win 7, Vista, XP, Windows 2000, Server 2003, Server 2008, Server 2008r2, Linux, Unix, AIX, SAP			
Environmental Advantages	ENERGY STAR® qualified, lower consumable materials and packaging, improved handling of recycled paper, faster power-up from sleep mode than laser printers			
Genuine TallyGenicom Cartridge Ribbons	Standard Life	17,000 pages		
	Extended Life*	30,000 pages	*Not compatible with 500 LPM printer models	
Paper Path/Handling	Straight paper path with easy-load adjustable tractors, paper-out detection and alarm, paper-motion detection and alarm			
Paper Type	Continuous, fan folded, edge-perforation			
Print Width	13.6" (345mm)			
Media Width	3" (76mm) to 17" (432mm)			
Media Copies	Up to 6 parts			
Media Weight	15 to 100 lbs up to 0.025" thickness 56 to 163 gm/m ² up to 0.64mm thickness			
MTBF*	10,000 hours at 25% duty cycle and 25% page density (*Mean Time Between Failures)			
Interfaces	Serial – RS-232 Parallel – IEEE-1284/Centronics Ethernet – PrintNet Suite 10/100 Base T (optional) Auto Switching – Between active ports			
Power Voltage	AC input range 88-270 VAC, 45 to 65 HZ			
Power Wattage (ENERGY STAR)	Less than 14 Watts in energy saving mode			
Power Wattage (typical)	6605/6605Q/6605Z	175 Watts	6615/6615Q/6615Z	390 Watts
	6610/6610Q/6610Z	260 Watts	6620Q	475 Watts



© 2011 Printronix, Inc. All rights reserved. Genicom, Tally, TallyGenicom, TG TallyGenicom, the TG Logo, Intellifilter, Intelliprint, PrintNet Suite, PrintNet Enterprise, PrintNet, Smart Ribbon and Printronix are trademarks or registered trademarks of Printronix, Inc. All other trademarks, product names, company names or logos herein are the property of their respective owners. Product appearance and/or specifications are subject to change without notice.
PTX_602A(7/12)



15345 Barranca Parkway, Irvine, CA 92618
1-800-665-6210 • www.tallygenicom.com